



Paper Type: Original Article

## Assessing Medical Waste Treatment Technique based on Hyperbolic fuzzy EMSWARA with COPRAS and ARAS Approaches

Nidhi Agarwal<sup>1</sup>, Palash Dutta<sup>1,\*</sup> 

<sup>1</sup>Department of Mathematics, Dibrugarh University, Dibrugarh, Assam, India; nidhiagarwal1906@gmail.com; Palash.dtt@gmail.com.

### Citation:

Received: 27 February 2025	Agarwal, N., & Dutta, P. (2025). Assessing medical waste treatment technique based on hyperbolic fuzzy EM-SWARA with COPRAS and ARAS approaches. <i>Uncertainty discourse and applications</i> , 2(3), 217-226.
Revised: 23 April 2025	
Accepted: 14 June 2025	

### Abstract

Medical Waste Treatment Techniques (MWTT) have become a significant concern due to the imminent risks they pose to human health and the environment. Proper and secure treatment and disposal of toxic and harmful medical waste are essential and various MWTT options are available to achieve this. The selection of the ideal MWT option is a complex and crucial Multi Criteria Decision Making (MCDM) problem as the decision is influenced by several factors both qualitative and quantitative aspects. This study presents a hybrid MCDM method for analyzing and opting the MWT options within a Hyperbolic fuzzy framework. The Hyperbolic Fuzzy Set (HyFS) is an advanced tool that addresses uncertainty with greater precision, providing more flexibility for the decision makers. An entropy measure and a score function have been introduced in a hyperbolic fuzzy environment. Objective weights are evaluated using the entropy measure while subjective weights are assessed through the Stepwise Weight Assessment Ratio Analysis (SWARA) model. Consequently, a pioneering hybrid MCDM approach is presented combining HyF-EM-SWARA with Complex Proportional Assessment (COPRAS) and Additive Ratio Assessment (ARAS) techniques to identify the optimal MWT option in India. Furthermore, relative evaluations and variability analysis are presented to demonstrate the stability and reliability of the proposed hybrid MCDM methods for ranking the preferences of MWTT.

**Keywords:** Hyperbolic fuzzy set, Entropy measure, Medical waste treatment.

## 1|Introduction

In our everyday lives, we are constantly faced with the need to make decisions, guided by a variety of conditions and pieces of information. Yet, this information often carries a certain vagueness and uncertainty, making over choices all the more challenging and intriguing. To address such situation, Zadeh[1] introduced fuzzy set theory (FST).

 Corresponding Author: Palash.dtt@gmail.com

 <https://doi.org/10.48313/uda.vi.63>

 Licensee System Analytics. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (<http://creativecommons.org/licenses/by/4.0>).

Which has numerous applications in real world domains, including risk assessment, operation research, medical diagnosis, decision making etc. FST assigns a value within the interval  $[0,1]$  to each element in a universal set known as membership value/degree of satisfaction( $\alpha$ ) while non-membership value/degree of dissatisfaction( $\beta$ ) as  $1 - \alpha$ . But the value of non-membership may not be always one minus the membership value. Due to these limitations, Atanassov [2] introduced the Intuitionistic fuzzy set (IFS), as a generalisation of FST. This framework imposes the condition that the sum of membership value  $\alpha$  and non-membership value  $\beta$  cannot exceed 1 i.e.,  $0 \leq \alpha + \beta \leq 1$  where  $\alpha, \beta \in [0, 1]$ . Nonetheless, in specific scenarios, where  $\alpha = 0.7$  and  $\beta = 0.4$ , this condition may not be met by IFS. Due to limitation of IFS, Yager[3] introduce the Pythagorean Fuzzy Set (PFS), a more adaptable framework. In the realm of PFS, the sum of the squares of membership and non-membership values is constrained to not exceed 1 i.e.,  $0 \leq \alpha^2 + \beta^2 \leq 1$ . However, it also has its own limitations. For instance, when one consider values such as  $\alpha = 0.7$  and  $\beta = 0.8$ , we find that this condition cannot be satisfied. Later, Yager[4] extended the PFS to q-rung orthopair fuzzy set (Q-ROFS), where the  $q^{th}$  sum of membership and non-membership values is restricted to not exceed 1 i.e.,  $0 \leq \alpha^q + \beta^q \leq 1$  where  $q \geq 1$ . Q-ROFS significantly expands the decision-making framework, providing greater flexibility compared to other existing fuzzy sets.

In practical scenarios, we often encounter situation where individuals experience complete satisfaction alongside partial dissatisfaction. This duality allows for a possibility of full membership coupled with partial non-membership or vice versa. To address this complexity, Dutta and Borah[5] proposed the Hyperbolic Fuzzy Set (HyFS), which serves as generalisation of IFS, PFS and Q-ROFS. In HyFS, the product of membership and non-membership values cannot exceed 1 i.e.,  $0 \leq \alpha \cdot \beta \leq 1$  thus providing significant flexibility and versatile framework for decision-makers, allowing for scenarios where  $\alpha = 1$  and  $\beta > 0$  or  $\alpha > 0$  and  $\beta = 1$ , where  $\alpha, \beta \in [0, 1]$ . None of the IFS, PFS and Q-ROFS can meet this nuanced requirement making HyFS as a significant advancement in the field of fuzzy sets.

In recent years, the global population has surged, bringing with it a dramatic rise in healthcare facilities and an ever-growing demand for medical services. Within this context, effective medical based treatment has become essential for protecting public health, preventing environmental pollution and ensuring compliance with regulatory standards. Healthcare facilities produce various types of waste, including infectious materials, hazardous substances and pharmaceuticals, all of which can pose serious risks if not managed properly. Ineffective waste management not only threatens our environment but also invites unpleasant odors and attracts pests, such as insects and rodents, which can facilitate the spread of diseases like bacterial infections, HIV and hepatitis. Therefore, selecting the appropriate medical waste treatment technology in crucial for ensuring safety, regulatory compliance, environmental sustainability and cost-effectiveness. The decision-making process in this area is complex and influenced by several factors that can effectively analysed using Multi-Criteria Decision-Making (MCDM) methods. To address this complexity, we propose an integrated framework that evaluates conflicting criteria based on expert assessments. Remarkably, no prior research has explored the application of hybrid MCDM methods within a hyperbolic fuzzy framework, making our approach innovative. Thus, we present the optimal medical waste treatment techniques identified through the HyF-EM-SWARA-COPRAS and HyF-EM-SWARA-ARAS approaches. This research aims to contribute to the development of improved strategies for managing medical waste, ensuring a safer and more sustainable environment.

## 1.1 Literature Review

Zadeh[1] introduced the concept of fuzzy set theory to address the issue of vagueness, uncertainty and imprecision inherent in real-life decision-making scenarios. Since then, numerous extensions of fuzzy sets have emerged, including IFS[2], PFS[3] and Q-ROFS[4], each serving as a generalization of traditional fuzzy sets. More recently, Dutta and Borah[5] have developed the HyFS which offers significant flexibility and enough space to the diverse need of decision-makers. The HyFS has garnered substantial interest among researchers focused on decision-making amidst the increasing complexity of contemporary challenges. Numerous studies have utilized HyFS to tackle a variety of MCDM problems. Divsalar et al[6] effectively applied HyFS to the sustainable supplier selection problem within the daily industry. Zavadskas et al[7] employed hyperbolic fuzzy data to establish personalized priorities for contract clauses. Additionally, Banik and Dutta[8] employed HyFS to identify crime-prone zones in Dibrugarh city.

The selection of optimal MWTT is crucial for safeguarding public health and protecting the environment. Extensive research has been conducted to identify the most effective strategies for enhancing MWTT, with fuzzy set theory being a key component of these studies. However, there is currently no published evaluations concerning MWTT assessment using the HyFS preference structure.

The MCDM methods established in fuzzy environment have demonstrated their efficacy in the selection process for MWTT, highlighting the necessity for further exploration and application of HyFS in this essential area. To address the significant challenges associated with MWTT through traditional decision-making methods[9, 10]. Dursun et al [11] have pioneered a MCDM technique within a fuzzy framework for MWT. Their work introduced two robust fuzzy MCDM frameworks, employing fuzzy integral and a hierarchical distance-based technique which represent a sustainable advancement in this field. Building on Dursun et al[11] insights, Liu et al[12] advanced the determining the optimal selection for MWT. This was followed by the development of an ILT-MULTIOORA technique by Liu et al[13] which utilizes interval 2-tuple linguistic variables. Liu et al[14] evaluated the weights of the criteria using the 2-tuple DAMETAL method and applied the fuzzy MULTIMOORA methodology to assess MWTT comprehensively. Lu et al[15] introduced an interval 2-tuple induced-TOPSIS method and Xiao[16] unveiled a technique for prioritizing MWTT that assigns crisp values to linguistic variables and leverages D-numbers integration for comprehensive assessment. Hinduja and Pandey[17] formulated a hybrid algorithm that enhances the selection for MWTT. Additionally, Li et al[18] contributed to the dialogue by proposing a hybrid MCDM technique that synergizes the DEMATEL and TOPSIS methods within an interval-valued fuzzy environment. Despite these advancements, a notable gap persists in the literature regarding methodologies that seamlessly integrate both objective and subjective weights for MWT attributes. Both weights plays a vital role in minimizing potential losses while enhancing decision accuracy. The MWT selection problem remains largely unexplored. There exists a significant gap in research utilizing an integrated entropy measure, SWARA model combined with COPRAS or ARAS approaches in a hyperbolic fuzzy environment. Therefore, this research proposes an innovative approach to MWTT selection within a hyperbolic fuzzy environment, effectively harnessing the strengths of both objective and subjective weights.

## 1.2 Motivations and Objectives

By employing MCDM, healthcare facility can adopt efficient solutions that not only comply with regulatory standards, but also advanced sustainability goals. This strategic approach is vital for safeguarding public health and protecting our environment for future generations. One constructive approach to enhancing contemporary MCDM techniques involves carefully establishing appropriate weights for various criteria.

In consideration of the preceding points, the following motivation drive this research :

1. Existing fuzzy set theories often encounter challenges in addressing certain paradoxical situations, creating a significant gap in the handling of uncertainty. The implementation of hyperbolic fuzzy set offers a sophisticated approach that allows for full membership, partial non-membership and their reversals.
2. Entropy measure and score functions plays a pivotal role in determining the weights of criteria and evaluate alternatives within MCDM models. These methodologies can facilitate the development of advanced MCDM techniques such as COPRAS, SAW, ARAS etc. Furthermore, there is no development of entropy measure within a hyperbolic fuzzy environment, highlighting a valuable opportunity for innovation in this area.
3. There is a significant lack of literature addressing the application of hybrid MCDM methods within the hyperbolic fuzzy context.

In consideration of the preceding points, the following are the objectives of this research :

1. Developing a novel score function for HyFS.
2. Developing an entropy measure for HyFS for determining the objective weight of the criteria.
3. A case study to endorse the probable impact of the proposed algorithm in MWTT selection using HyFS.

## 1.3 Structure of the paper

The structure of this paper is organized as follows :

In section 2, we provide the definitions of existing fuzzy sets, including IFS, PFS, Q-ROFS and HyFS with some basic operations on HyFS. Section 3 presents a novel entropy measure, score function within hyperbolic fuzzy environment and the algorithms for the EM-SWARA-COPRAS and EM-SWARA-ARAS methods under the HyFSs context. Section 4 demonstrates the practical application of the developed methodology through a case study on selecting the most desirable MWTT option in India. The case study illustrates the strength and robustness of the proposed approach. Also, a comparative

analysis is presented that underscores its advantages. Finally, section 5 conclude the paper and outlines future research scope.

## 2|Preliminaries

This section summarizes some of the definitions and notations necessary for a comprehensive understanding of the study.

**Definition 1.** [4] Let,  $X = \{x_1, x_2, \dots, x_n\}$  represents a Universe of Discourse. A q-rung orthopair fuzzy set (Q-ROFS) Q on X is defined by  $Q = \{(x_i, \alpha_Q(x_i), \beta_Q(x_i)) | x_i \in X\}$  where  $\alpha_Q: X \rightarrow [0, 1]$  denotes the membership function and  $\beta_Q: X \rightarrow [0, 1]$  denotes the non-membership function of the element  $x_i \in X$  with the restriction  $0 \leq (\alpha_Q(x_i))^q + (\beta_Q(x_i))^q \leq 1$  where  $q \geq 1$ .

The degree of hesitancy is determined by  $\pi_Q(x_i) = \{1 - \alpha_Q(x_i)^q - (\beta_Q(x_i))^q\}^{\frac{1}{q}}$ .

**Definition 2.** A q-rung orthopair fuzzy set is classified as follows :

Intuitionistic Fuzzy Set (IFS)[2] if  $q = 1$  i.e., having the condition  $0 \leq (\alpha_Q(x_i)) + (\beta_Q(x_i)) \leq 1$

Pythagorean Fuzzy Set(PFS)[3] if  $q = 2$  i.e., having the condition  $0 \leq (\alpha_Q(x_i))^2 + (\beta_Q(x_i))^2 \leq 1$

Fermatean Fuzzy Set(FFS)[43] if  $q = 3$  i.e., having the condition  $0 \leq (\alpha_Q(x_i))^3 + (\beta_Q(x_i))^3 \leq 1$

Quartic Fuzzy Set(QrFS)[44] if  $q = 4$  i.e., having the condition  $0 \leq (\alpha_Q(x_i))^4 + (\beta_Q(x_i))^4 \leq 1$

Quintic Fuzzy Set(QnFS)[45] if  $q = 5$  i.e., having the condition  $0 \leq (\alpha_Q(x_i))^5 + (\beta_Q(x_i))^5 \leq 1$

**Definition 3.** [5] Let,  $X = \{x_1, x_2, \dots, x_n\}$  represents a Universe of Discourse. A Hyperbolic Fuzzy Set (HyFS)  $\Lambda$  on X is defined by  $H = \{(x_i, \alpha_\Lambda(x_i), \beta_\Lambda(x_i)) | x_i \in X\}$  where  $\alpha_\Lambda: X \rightarrow [0, 1]$  denotes the membership function and  $\beta_\Lambda: X \rightarrow [0, 1]$  denotes the non-membership function of the element  $x_i \in X$  with the restriction  $0 \leq (\alpha_\Lambda(x_i)).(\beta_\Lambda(x_i)) \leq 1$ .

**Definition 4.** Let,  $\Lambda_1 = (\alpha_1, \beta_1)$  and  $\Lambda_2 = (\alpha_2, \beta_2)$  be two HyFSs with  $\lambda > 0$ . Then, the operations on HyFSs are defined as follows:

(i)  $\Lambda_1 \cup \Lambda_2 = (max\{\alpha_1, \alpha_2\}, min\{\beta_1, \beta_2\})$ .

(ii)  $\Lambda_1 \cap \Lambda_2 = (min\{\alpha_1, \alpha_2\}, max\{\beta_1, \beta_2\})$ .

(iii)  $\Lambda_1^C = (1 - \alpha_1, 1 - \beta_1)$ .

(iv)  $\Lambda_1 \oplus \Lambda_2 = (\alpha_1 + \alpha_2 - \alpha_1\alpha_2, \beta_1\beta_2)$ .

(v)  $\Lambda_1 \otimes \Lambda_2 = (\alpha_1\alpha_2, \beta_1 + \beta_2 - \beta_1\beta_2)$ .

(vi)  $\lambda\Lambda_1 = (1 - (1 - \alpha_1)^\lambda, \beta_1^\lambda)$ .

(vii)  $\Lambda_1^\lambda = (\alpha_1^\lambda, 1 - (1 - \beta_1^\lambda))$ .

(viii)  $\Lambda_1 \subseteq \Lambda_2$  iff  $\alpha_1 \leq \alpha_2$  and  $\beta_1 \geq \beta_2$ .

**Definition 5.** Let,  $\Lambda_i = (\alpha_i, \beta_i), i = 1, 2, \dots, n$  be HyFSs. Then, the hyperbolic fuzzy weighting averaging operator (HyFWAO) is defined as

$$HyFWA_w(\alpha_1, \alpha_2, \dots, \alpha_n) = w_j \alpha_j = \bigoplus_{j=1}^n (1 - \prod_{j=1}^n (1 - \alpha_j) w_j, \prod_{j=1}^n (\beta_j) w_j)$$

where  $w = (w_1, w_2, \dots, w_n)^T$  is a weight vector for  $\alpha_j$  and  $\sum_{j=1}^n w_j = 1$  with  $0 \leq w_j \leq 1, i = 1, 2, \dots, n$ .

## 3|Proposed Work

This section presents a novel entropy measure and a score function within the hyperbolic fuzzy framework, making a significant advancement in MCDM techniques.

### 3.1|A Novel Hyperbolic Fuzzy Entropy Measure

The entropy measure plays a pivotal role in the development of MCDM techniques, as it is essential for identifying the objective weight of attributes. Despite its importance, the hyperbolic fuzzy framework has lacked a suitable entropy measure until now.

**Definition 5.** Let, HyFN  $H = (x, y)$  such that  $x, y \in [0, 1]$  and  $0 \leq x.y \leq 1$ .

A function  $E: HyFS(X) \rightarrow [0, 1]$  is a HyF entropy measure if

(i)  $E(H) = 0$  if  $H$  is a crisp set.

(ii)  $E(H)$  attains its unique maximum when  $x = y = \frac{1}{2}$

(iii)  $E(H) = E(H^C)$

(iv)  $E(H_1) \leq E(H_2)$  if  $H_1$  is crisper than  $H_2$ , i.e.,  $x_1 \leq x_2 \leq \frac{1}{2}, y_1 \leq y_2 \leq \frac{1}{2}$  or  $x_1 \geq x_2 \geq \frac{1}{2}, y_1 \geq y_2 \geq \frac{1}{2}$  where  $H_1 = (x_1, y_1)$  and  $H_2 = (x_2, y_2)$

A novel HyF entropy measure is proposed as given below :

$$E_{NP}(H) = 1 - \frac{(2x + 2y - 2)}{xy + 1}. \quad (1)$$

**Theorem 1.** The function  $E_{NP}(\Lambda)$  is an HyF entropy measure.

### 3.2|A Novel Hyperbolic Fuzzy Score Function

We propose a novel score function with the following definitions :

**Definition 6.** Let,  $H = (x, y)$  be a HyFN, then the score function  $S_{NP}$  of  $H$  is defined as

$$S_{NP}(H) = \frac{xy + x + 1}{2(y + 1)}. \quad (2)$$

where  $S_{NP}(H) \in [0, 1]$

## 4|Application in MWTT Selection

Medical waste treatment has experienced considerable advancement in recent years due to the growing recognition of public health and environmental imperatives. Various case studies in developing countries have been conducted to identify the optimal MWTT. This study aims to rigorously evaluate the available alternatives for MWT in order to determine the most effective option. The study outlines five prominent technique  $A_1$ : autoclaving,  $A_2$ : microwave,  $A_3$ : plasma pyrolysis,  $A_4$ : chemical disinfection,  $A_5$ : incineration for MWT in India, which are assessed against ten critical criteria. A team of four experts  $\{E_1, E_2, E_3, E_4\}$  is assembled who provided valuable insights into the significance of each criteria[46, 20]. The linguistic variables matrix employed to evaluate the criteria is detailed in Table 1. The experts evaluations of LVs are summarized in Table 2. To effectively rank the MWTTs, the proposed HyF-EM-SWARA-COPRAS and HyF-EM-SWARA-ARAS algorithms are utilized. Moreover, this study is pioneering as it employs a hybrid MCDM method within a hyperbolic fuzzy framework for the selection of MWTT. This research seeks to make a meaningful contribution to the field of medical waste management and public health.

Table 1. LVs for the criteria based on HyFNs.

Importance	HyFNs
Extremely good (EG)	(1,0)
Very good (VG)	(0.95,0.05)
Good (G)	(0.75,0.20)
Medium good (MG)	(0.65,0.30)
Fair (F)	(0.55,0.40)
Medium poor (MP)	(0.40,0.50)
Poor (P)	(0.30,0.60)
Very poor (VP)	(0.20,0.70)
Extremely poor (EP)	(0.10,0.80)

Table 2. LVs for the level of significance of DEs.

Importance	HyFNs
Extremely significant	(1,0)
Very significant	(0.90,0.05)
Significant	(0.70,0.20)
Moderate	(0.60,0.30)
Insignificant	(0.40,0.50)
Very insignificant	(0.30,0.80)
Extremely insignificant	(0.10,0.80)

Table 3. HyF linguistic decision matrix by DEs.

Alternatives	Experts	C r i t e r i a									
		$C_1$	$C_2$	$C_3$	$C_4$	$C_5$	$C_6$	$C_7$	$C_8$	$C_9$	$C_{10}$
$A_1$	$E_1$	G	P	P	VG	F	F	F	VG	G	VG
	$E_2$	F	MG	F	G	MG	P	G	P	VP	G
	$E_3$	MP	G	P	P	G	P	VG	F	MG	VG
$A_2$	$E_4$	F	F	P	P	P	VG	MG	F	G	MG
	$E_1$	VG	VP	F	G	F	MP	VG	G	G	VG
	$E_2$	P	G	F	G	MG	P	G	F	MP	MG
	$E_3$	F	MG	P	MP	G	MG	G	MG	F	G
$A_3$	$E_4$	F	MG	VP	P	MP	G	VG	F	VG	P
	$E_1$	G	VP	F	G	F	MP	VG	G	G	VG
	$E_2$	P	G	G	G	P	F	F	F	P	VG
	$E_3$	F	G	P	P	G	MP	F	F	F	G
$A_4$	$E_4$	P	VP	F	VP	MG	G	G	G	MG	MP
	$E_1$	V	MP	MG	G	MG	MG	P	VG	MG	F
	$E_2$	P	MG	F	MG	MG	G	MG	G	P	MG
	$E_3$	F	F	P	P	VG	MP	F	G	F	MG
$A_5$	$E_4$	F	P	VP	P	MP	G	G	VG	D	MP
	$E_1$	VG	G	F	VG	F	MG	F	VG	MG	G
	$E_2$	VG	VG	MG	F	MG	G	MG	MG	G	G
	$E_3$	P	P	G	P	G	MP	F	G	P	MP
	$E_4$	P	P	MG	MG	MP	F	F	G	F	P

Table 4. Weights of the .

DEs	$E_1$	$E_2$	$E_3$	$E_4$
Ratings	Significant	Moderate	Very significant	Insignificant
HyFNs	(0.70,0.20)	(0.60,0.30)	(0.90,0.05)	(0.40,0.50)
Weights ( $v_k$ )	0.2697	0.2259	0.3555	0.1489

Table 5. Aggregated HyF-DM.

	$A_1$	$A_2$	$A_3$	$A_4$	$A_5$
$C_1$	(0.5746,0.3592)	(0.7251,0.2502)	(0.5468,0.3863)	(0.7251,0.2502)	(0.8017,0.1751)
$C_2$	(0.6113,0.3268)	(0.5946,0.3440)	(0.5932,0.3379)	(0.5093,0.4229)	(0.7079,0.2545)
$C_3$	(0.3665,0.5475)	(0.4264,0.5022)	(0.4806,0.4407)	(0.4640,0.4647)	(0.6677,0.2807)
$C_4$	(0.7277,0.2395)	(0.6022,0.3262)	(0.5713,0.3562)	(0.5466,0.3815)	(0.7196,0.2526)
$C_5$	(0.6315,0.3112)	(0.6399,0.3029)	(0.6683,0.2723)	(0.8101,0.1712)	(0.6399,0.3029)
$C_6$	(0.5805,0.3715)	(0.5498,0.3791)	(0.5065,0.4148)	(0.6263,0.3090)	(0.5921,0.3426)
$C_7$	(0.8262,0.1565)	(0.8725,0.1119)	(0.5355,0.4025)	(0.5612,0.3771)	(0.5748,0.3748)
$C_8$	(0.7251,0.2502)	(0.6488,0.2995)	(0.6482,0.2993)	(0.8725,0.1119)	(0.8252,0.1508)
$C_9$	(0.6336,0.3066)	(0.7045,0.2560)	(0.5912,0.3484)	(0.5354,0.4056)	(0.5692,0.3656)
$C_{10}$	(0.9039,0.0893)	(0.7963,0.1776)	(0.7832,0.1870)	(0.5942,0.3498)	(0.6022,0.3262)

The weights of the DEs are calculated with the results presented in Table 3. For each alternative based on the criteria, a HyF decision matrix is developed by the panel of experts as illustrated in Table 4. The AHyF-DM is then constructed using DE's weight. The integrated weights for the criteria are determined by combining objective and subjective weights. The objective weights are derived using the Entropy Measure. The entropy values are calculated by employing equation(1) and Table 5. The objective weight is evaluated as follows :

$$O_j = \{0.0924, 0.1141, 0.1315, 0.1046, 0.0903, 0.1248, 0.0905, 0.0686, 0.1135, 0.0697\}$$

Table 6. The importance of criteria by the DEs.

	$E_1$	$E_2$	$E_3$	$E_4$	Aggregated HyFNs	Score Values
$C_1$	MP	F	P	MP	(0.4061,0.5073)	0.2643
$C_2$	P	VP	F	VP	(0.3710,0.5504)	0.2336
$C_3$	P	P	F	VP	(0.3897,0.5315)	0.2486
$C_4$	VG	MG	VG	G	(0.9014,0.0921)	0.8354
$C_5$	VG	G	VG	G	(0.9086,0.0841)	0.8474
$C_6$	F	G	G	MP	(0.6663,0.2764)	0.5197
$C_7$	VG	MG	MG	G	(0.8030,0.1742)	0.6898
$C_8$	G	G	MG	VG	(0.7783,0.1879)	0.6584
$C_9$	P	MP	P	VP	(0.3014,0.5892)	0.1898
$C_{10}$	VP	P	VP	MP	(0.2563,0.6430)	0.1566

Table 7. Subjective weights of criteria by HyF-SWARA technique.

		$z_j$	$k_j$	$p_j$	$S_j$
$C_5$	0.8474	-	1	1	0.1264
$C_4$	0.8354	0.0120	1.0120	0.9881	0.1249
$C_7$	0.6898	0.1456	1.1456	0.9763	0.1234
$C_8$	0.6584	0.0314	1.0314	0.9466	0.1197
$C_6$	0.5197	0.1387	1.1387	0.8313	0.1051
$C_1$	0.2643	0.2554	1.2554	0.6622	0.0837
$C_3$	0.2486	0.0157	1.0157	0.6520	0.0825
$C_2$	0.2336	0.0150	1.0150	0.6424	0.0812
$C_9$	0.1898	0.0438	1.0438	0.6154	0.0778
$C_{10}$	0.1566	0.0332	1.0332	0.5956	0.0753

The SWARA model is employed to determine the subjective weights of the criteria. The subjective weight of the criteria are determined using SWARA model is presented in the last column of Table 7. Finally, the integrated/final weights of the criteria are determined. The final weights of the criteria are presented as follows :  
 $w_j = \{0.1094, 0.1195, 0.1275, 0.1121, 0.0977, 0.1043, 0.0865, 0.0749, 0.0956, 0.0725\}$

Initially, the COPRAS method is applied to assess the alternative for MWT methods in India. The relative grade and utility grade are presented in Table 8. The results in Table 8 distinctly indicates that the ranking order for MWTT is  $A_1 > A_2 > A_4 > A_3 > A_5$ . Alternative  $A_1$  emerges as the best option for MWTT.

Moreover, we strengthen our analysis by applying the ARAS method within hyperbolic fuzzy framework. Table 12 shows that the alternatives are ranked as  $A_1 > A_2 > A_4 > A_3 > A_5$ . Thus,  $A_1$  is the best option for MWTT.

Table 8. Findings of the HyF-EM-SWARA-COPRAS method.

	$A_1$	$A_2$	$A_3$	$A_4$	$A_5$
$M_i$	(0.5044,0.4632)	(0.4890,0.4709)	(0.4069,0.5432)	(0.4670,0.4937)	(0.4203,0.5313)
$S(M_i)$	0.3356	0.3255	0.2543	0.3030	0.2650
$N_i$	(0.3367,0.2037)	(0.3452,0.1935)	(0.3110,0.2024)	(0.3260,0.2060)	(0.4551,0.1226)
$S(N_i)$	0.3245	0.3326	0.3118	0.3182	0.4220
$Q_i$	0.6913	0.6705	0.6245	0.6657	0.5385
$U_i$	<b>100</b>	<b>96.94</b>	<b>90.34</b>	<b>96.30</b>	<b>77.90</b>

Table 9. The normalized aggregated HyF-DM ( $X$ ).

	$A_1$	$A_2$	$A_3$	$A_4$	$A_5$
$C_1$	(0.4254,0.6408)	(0.2749,0.7498)	(0.4532,0.6137)	(0.2749,0.7498)	(0.1983,0.8249)
$C_2$	(0.3887,0.6732)	(0.4054,0.6560)	(0.4068,0.6621)	(0.4907,0.5771)	(0.2921,0.7455)
$C_3$	(0.6335,0.4525)	(0.5736,0.4978)	(0.5194,0.5593)	(0.5360,0.5353)	(0.3323,0.7193)
$C_4$	(0.2723,0.7605)	(0.3978,0.6738)	(0.4287,0.6438)	(0.4535,0.6185)	(0.2804,0.7474)
$C_5$	(0.6315,0.3112)	(0.6399,0.3029)	(0.6683,0.2723)	(0.8101,0.1712)	(0.6399,0.3029)
$C_6$	(0.5805,0.3715)	(0.5498,0.3791)	(0.5065,0.4148)	(0.6263,0.3090)	(0.5921,0.3426)
$C_7$	(0.8262,0.1565)	(0.8725,0.1119)	(0.5355,0.4025)	(0.5612,0.3771)	(0.5748,0.3748)
$C_8$	(0.7251,0.2502)	(0.6488,0.2995)	(0.5482,0.2993)	(0.8725,0.1119)	(0.8252,0.1508)
$C_9$	(0.6336,0.3066)	(0.7045,0.2560)	(0.5912,0.3484)	(.5354,0.4056)	(0.5692,0.3656)
$C_{10}$	(0.9039,0.0893)	(0.7963,0.1776)	(0.7832,0.1870)	(0.5942,0.3498)	(0.6022,0.3262)

Table 10. Findings of the HyF-EM-SWARA-ARAS method.

	$A_1$	$A_2$	$A_3$	$A_4$	$A_5$	$X_0$
$C_1$	0.0237	0.0142	0.0259	0.0142	0.0096	0.0259
$C_2$	0.0230	0.0243	0.0242	0.0318	0.0164	0.0318
$C_3$	0.0506	0.0433	0.0366	0.0388	0.0202	0.0506
$C_4$	0.0142	0.0220	0.0244	0.0264	0.0148	0.0264
$C_5$	0.0446	0.0456	0.0496	0.0723	0.0456	0.0723
$C_6$	0.0409	0.0386	0.0344	0.0474	0.0431	0.0474
$C_7$	0.0672	0.0797	0.0303	0.0325	0.0333	0.0797
$C_8$	0.0426	0.0355	0.0354	0.0687	0.0583	0.0687
$C_9$	0.0440	0.0525	0.0391	0.0334	0.0370	0.0525
$C_{10}$	0.0749	0.0513	0.0493	0.0296	0.0308	0.0749
$E_i$	0.4257	0.4070	0.3491	0.3951	0.3091	0.5302
$F_i$	<b>0.8029</b>	<b>0.7676</b>	<b>0.6584</b>	<b>0.7452</b>	<b>0.5830</b>	

*Comparative Analysis.* In this section, we present comparison of our proposed technique against existing methodologies, demonstrating the efficacy and advantage of our developed approach for MWTT selection.

In comparison with other developed methodologies for MWTT selection, our approach demonstrates the following strengths :

1. Methodologies[12, 28, 46, 47, 49, 50] focuses solely on objective weights, disregarding subjective evaluations while methodologies[14, 16, 19, 22, 48, 51] emphasizes subjective weights, disregarding objective weights. This imbalance results in a flawed evaluation, allowing decision-makers to harness valuable human insight while maintaining rigorous analytical standards.
2. In methodologies[14, 16, 28, 47, 49, 50] weights assigned to experts are assumed randomly rather than meticulously computed, resulting in potentially biased and unrealistic outcomes. In critical fields like healthcare and medical waste management such oversights can have profound consequences. Our proposed methodology methodically computes expert weights, ensuring accuracy and reliability.
3. Methodologies[16, 20, 51] neglects the critical nature of attributes which can adversely affect the ranking of alternatives. Our proposed methodology rigorously accounts for these attributes, enhancing the credibility of the results.
4. Additionally, the findings by methodologies[21, 22] which positioned alternative  $A_5$  as the second-best option for MWTT, are equally questionable. This option is characterized by harmful emissions, being costly and sustainable energy consumption, all factors that undermining it viability.

## 5|Conclusion

Hyperbolic fuzzy sets constitutes a novel extension of fuzzy sets, characterized by greater flexibility and independence compared to traditional fuzzy set models. Notably, there has been a lack of entropy measures specifically tailored for HyFSs. To address this gap, an innovative hyperbolic entropy measure have been introduced, along with a new hyperbolic score function that proves to be more logical and reliable than current counterparts. Despite the potential benefits of hybrid methods in hyperbolic fuzzy environment, research in this area has been limited. In response, we present two comprehensive MCDM algorithms : HyF-EM-SWARA-COPRAS and HyF-EM-SWARA-ARAS. The results illustrate that the proposed frameworks effectively address the complexities associated with MWT options, yielding results that are both logical and intuitive for human decision-making.

The selection of an appropriate and effective MWTT has merged as a critical issue in the management of medical waste. This study seeks to addresses the pressing need for an effective method of selecting the optimal MWTT in India. The resulting ranking not only affirms our conclusions but also highlights the superiority of the proposed model. This evidence underscores the necessity for adopting best practices in MWT to promote public health and environmental safety.

Moreover, the HyF-EM-SWARA-COPRAS and HyF-EM-SWARA-ARAS methodologies can be effectively utilized for MCDM challenges. Their application extends to critical areas such as sustainable supplier selection in healthcare, optimizing energy sources for hospitals or even effectively triaging COVID-19 patients. To enhance the effectiveness of the MCDM technique, the additional weight measurement methods AHP, MEREC, CRITIC, BWM and DEMATEL can be incorporated. We can innovate a novel distance measure for HyFSs which can be applied to other MCDM methods such as TOPSIS, EDAS and VIKOR. This strategic approach will significantly elevate the precision and versatility of decision-making processes.

## Authors' Contributions

N. A.: Writing-original draft, Methodology, Conceptualization, and Formal Analysis P. D.: Research Design, Computing, Visualization, Writing-Review & Editing and Validation. The authors have read and agreed to the published version of the manuscript.

## Data Availability

All data are included in the text.

## Funding

This research received no external funding.

## Conflict of Interest

The authors declare that in this paper, there is no conflict of interests.

## Consent for Publication

The authors have given consent for the publication of this manuscript.

## Ethics Approval and Consent to Participate

This study does not involve any research conducted on human participants or animals.

## References

- [1] Zadeh, L. A. (1965). Fuzzy sets. *Information and Control*, 8(3), 338–353. [http://dx.doi.org/10.1016/S0019-9958\(65\)90241-X](http://dx.doi.org/10.1016/S0019-9958(65)90241-X)
- [2] Atanassov, K. T. (1986). Intuitionistic fuzzy sets. *Fuzzy Sets and Systems*, 20(1), 87–96. [http://dx.doi.org/10.1016/S0165-0114\(86\)80034-3](http://dx.doi.org/10.1016/S0165-0114(86)80034-3)
- [3] Yager, R. R. (2013). Pythagorean fuzzy subsets. In 2013 Joint IFSA World Congress and NAFIPS Annual Meeting (IFSA/NAFIPS) (pp. 57–61). IEEE. <https://doi.org/10.1109/IFSA-NAFIPS.2013.6608375>
- [4] Yager, R. R. (2017). Generalized orthopair fuzzy sets. *IEEE Transactions on Fuzzy Systems*, 25(5), 122–130. <https://doi.org/10.1109/TFUZZ.2016.2604005>
- [5] Dutta, P., & Borah, G. (2023). Construction of hyperbolic fuzzy set and its application in diverse COVID-19 associated problems. *New Mathematics and Natural Computation*, 19(1), 217–289.
- [6] Divsalar, M., Ahmadi, M., Ghaedi, M., & Ishizaka, A. (2023). An extended TODIM method under a hyperbolic fuzzy environment. *Computers & Industrial Engineering*. <https://doi.org/10.1016/j.cie.2023.109655>
- [7] Zavadskas, E. K., Krishankumar, R., Ravichandran, K. S., Vilkonis, A., & Antuceviciene, J. (2025). Hyperbolic fuzzy set decision framework for construction contracts integrating CRITIC and WASPAS for dispute mitigation. *Automation in Construction*, 174, 106137. <https://doi.org/10.1016/j.autcon.2025.106137>
- [8] Banik, A. K., & Dutta, P. (2024). An efficient decision-making method based on hyperbolic fuzzy environment with new score function and its application in determining crime-prone zones. *International Journal of Machine Learning and Cybernetics*. <https://doi.org/10.1007/s13042-024-02404-z>
- [9] Brent, A. C., Rogers, D. E., Ramabitsa-Siimane, T. S., & Rohwer, M. B. (2007). Application of the analytical hierarchy process to establish health care waste management systems that minimise infection risks in developing countries. *European Journal of Operational Research*, 181(1), 403–424. <https://doi.org/10.1016/j.ejor.2006.06.015>
- [10] Diaz, L., Savage, G., & Eggerth, L. (2005). Alternatives for the treatment and disposal of healthcare wastes in developing countries. *Waste Management*, 25(6), 626–637. <https://doi.org/10.1016/j.wasman.2005.01.005>
- [11] Dursun, M., Karsak, E. E., & Karadayi, M. A. (2011). Assessment of health-care waste treatment alternatives using fuzzy multi-criteria decision-making approaches. *Resources, Conservation and Recycling*, 57, 98–107. <https://doi.org/10.1016/j.resconrec.2011.09.012>
- [12] Liu, H. C., Wu, J., & Li, P. (2013). Assessment of health-care waste disposal methods using a VIKOR-based fuzzy multi-criteria decision-making method. *Waste Management*, 33(12), 2744–2751. <https://doi.org/10.1016/j.resconrec.2011.09.012>
- [13] Liu, H. C., You, J. X., & Shan, M. M. (2014). Application of interval 2-tuple linguistic MULTIMOORA method for health-care waste treatment technology evaluation and selection. *Waste Management*, 34(11), 2355–2364. <https://doi.org/10.1016/j.resconrec.2011.09.012>
- [14] Liu, H. C., You, J. X., Lu, C., & Chen, Y. Z. (2015). Evaluating health-care waste treatment technologies using a hybrid multi-criteria decision-making model. *Renewable and Sustainable Energy Reviews*, 41, 932–942. <https://doi.org/10.1016/j.rser.2014.08.061>
- [15] Lu, C., You, J. X., Liu, H. C., & Li, P. (2016). Health-care waste treatment technology selection using the interval 2-tuple induced TOPSIS method. *International Journal of Environmental Research and Public Health*, 13(6), 562. <https://doi.org/10.3390/ijerph13060562>
- [16] Xiao, F. (2018). A novel multi-criteria decision-making method for assessing health-care waste treatment technologies based on D numbers. *Engineering Applications of Artificial Intelligence*, 71, 216–225. <https://doi.org/10.1016/j.engappai.2018.03.002>
- [17] Hinduja, A., & Pandey, M. (2018). Assessment of healthcare waste treatment alternatives using an integrated decision support framework. *International Journal of Computational Intelligence Systems*, 12(1), 318. <https://doi.org/10.2991/ijcis.2018.125905685>

- [18] Li, H., Li, J., Zhang, X., Cao, X., Zhu, J., & Chen, W. (2020). Establishing an interval-valued fuzzy decision-making method for sustainable selection of healthcare waste treatment technologies in emerging economies. *Journal of Material Cycles and Waste Management*, 22 (2), 501–514. <https://doi.org/10.1007/s10163-019-00943-0>
- [19] Manupati, V. K., Ramkumar, M., Baba, V., & Agarwal, A. (2021). Selection of the best healthcare waste disposal techniques during and post COVID-19 pandemic era. *Journal of Cleaner Production*, 281, 125175. <https://doi.org/10.1016/j.jclepro.2020.125175>
- [20] Liu, P., Rani, P., & Mishra, A. R. (2021). A novel Pythagorean fuzzy combined compromise solution framework for the assessment of medical waste treatment technology. *Journal of Cleaner Production*, 292, 126047. <https://doi.org/10.1016/j.jclepro.2021.126047>
- [21] Saha, A., Mishra, A. R., Rani, P., Hezam, L. M., & Cavallaro, F. (2022). A q-rung orthopair fuzzy FUCOM double normalization-based multi-aggregation method for healthcare waste treatment method selection. *Sustainability*, 14(7), 4171. <https://doi.org/10.3390/su14074171>
- [22] Krishankumar, R., Mishra, A. R., Rani, P., Zavadskas, E. K., Ravichandran, K., & Kar, S. (2022). A new decision model with integrated approach for healthcare waste treatment technology selection with generalized orthopair fuzzy information. *Information Sciences*, 610, 1010–1028. <https://doi.org/10.1016/j.ins.2022.08.022>
- [23] Yang, Y. D., & Ding, X. F. (2023). Emergency response scheme selection with T-spherical hesitant probabilistic fuzzy TODIM-TPZSG approach. *Engineering Applications of Artificial Intelligence*, 123, 105777. <https://doi.org/10.1016/j.engappai.2023.106190>
- [24] Liu, J., Liu, P., Liu, S. F., Zhou, X. Z., & Zhang, T. (2015). A study of decision process in MCDM problems with large number of criteria. *International Transactions in Operational Research*, 22, 237–264. <https://doi.org/10.1111/itor.12102>
- [25] Diakoulaki, D., Mavrotas, G., & Papayannakis, L. (1995). Determining objective weights in multiple criteria problems: The CRITIC method. *Computers & Operations Research*, 22, 763–770. [https://doi.org/10.1016/0305-0548\(94\)00059-H](https://doi.org/10.1016/0305-0548(94)00059-H)
- [26] Goldstein, W. M. (1990). Judgements of relative importance in decision making: Global vs local interpretations of subjective weight. *Organizational Behavior and Human Decision Processes*, 47, 313–336. [https://doi.org/10.1016/0749-5978\(90\)90041-7](https://doi.org/10.1016/0749-5978(90)90041-7)
- [27] Kersulienė, V., Zavadskas, E., & Turskis, Z. (2010). Selection of rational dispute resolution method by applying new step-wise weight assessment ratio analysis (SWARA). *Journal of Business Economics and Management*, 11, 243–258. <https://www.tandfonline.com/doi/abs/10.3846/jbem.2010.12>
- [28] Joshi, D., & Kumar, S. (2014). Intuitionistic fuzzy entropy and distance measure based TOPSIS method for multi-criteria decision making. *Egyptian Informatics Journal*, 15(2), 97–104. <https://doi.org/10.1016/j.eij.2014.03.002>
- [29] De Luca, A., & Termini, S. (1972). A definition of a nonprobabilistic entropy in the setting of fuzzy sets theory. *Information and Control*, 20(4), 301–312. <https://doi.org/10.1016/B978-1-4832-1450-4.50020-1>  
Get rights and content
- [30] Szmidt, E., & Kacprzyk, J. (2001). Entropy for intuitionistic fuzzy sets. *Fuzzy Sets and Systems*, 118(3), 467–477. [https://doi.org/10.1016/S0165-0114\(98\)00402-3](https://doi.org/10.1016/S0165-0114(98)00402-3)
- [31] Chen, S. M., & Tan, J. M. (1994). Handling multicriteria fuzzy decision-making problems based on vague set theory. *Fuzzy Sets and Systems*, 67(2), 163–172. [https://doi.org/10.1016/0165-0114\(94\)90084-1](https://doi.org/10.1016/0165-0114(94)90084-1)
- [32] Zavadskas, E., & Turskis, Z. (2010). A new additive ratio assessment (ARAS) method in multicriteria decision-making. *Technological and Economic Development of Economy*, 16(2), 159–172. [https://doi.org/10.1016/0165-0114\(94\)90084-1](https://doi.org/10.1016/0165-0114(94)90084-1)
- [33] Zavadskas, E. K., Turskis, Z., & Viltiene, T. (2010). Multi criteria analysis of foundation instalment alternatives by applying additive ratio assessment (ARAS) method. *Archives of Civil and Mechanical Engineering*, 10(3), 123–141. [https://doi.org/10.1016/S1644-9665\(12\)60141-1](https://doi.org/10.1016/S1644-9665(12)60141-1)
- [34] Karabasevic, D., Zavadskas, E., Turskis, Z., & Stanujkic, D. (2016). The framework for the selection of personnel based on the SWARA and ARAS methods under uncertainties. *Informatica*, 27, 49–56. <https://doi.org/10.3233/INF-2016-1090>
- [35] Medineckiene, M., Zavadskas, E., Björka, F., & Turskis, Z. (2015). Multicriteria decision-making system for sustainable building assessment/certification. *Archives of Civil and Mechanical Engineering*, 15(1), 11–18. <https://doi.org/10.1016/j.acme.2014.09.001>
- [36] Mishra, A. R., Sisodia, G., Pardasani, K. R., & Sharma, K. (2020). Multi-criteria IT personnel selection on intuitionistic fuzzy information measures and ARAS methodology. *Iranian Journal of Fuzzy Systems*, 17(4), 55–68. [https://ijfs.usb.ac.ir/article\\_5406\\_773e304765eeced9372865246c596bf2a.pdf](https://ijfs.usb.ac.ir/article_5406_773e304765eeced9372865246c596bf2a.pdf)
- [37] Bakshi, T., & Sinharay, A. (2011). An integrated novel approach in MCDM under fuzziness. *International Journal of Computer and Communication Technology*, 2(7), 36–43. <https://core.ac.uk/download/pdf/480907033.pdf>
- [38] Bakshi, T., & Sarkar, B. (2011). MCA based performance evaluation of project selection. *International Journal of Software Engineering and Applications*, 2(2), 14–22. <https://core.ac.uk/download/pdf/480907033.pdf>
- [39] Zavadskas, E. K., Kaklauskas, A., & Sarka, V. (1994). The new method of multicriteria complex proportional assessment of projects. *Technological and Economic Development of Economy*, 1, 131–139. <https://etalpykla.vilniustech.lt/handle/123456789/111916>
- [40] Organ, A., & Yalçın, E. (2016). Performance evaluation of research assistants by COPRAS method. *European Scientific Journal*, 12, 102–109. <https://B2n.in/tx2013>
- [41] Hezer, S., Gelme, E., & Özceylan, E. (2021). Comparative analysis of TOPSIS, VIKOR and COPRAS methods for the COVID-19 regional safety assessment. *Journal of Infection and Public Health*, 14, 775–786. <https://doi.org/10.1016/j.jiph.2021.03.003>
- [42] Sahabuddin, M., & Khan, I. (2021). Multi-criteria decision analysis methods for energy sector's sustainability assessment: Robustness analysis through criteria weight change. *Sustainable Energy Technologies and Assessments*, 47, 101380. <https://doi.org/10.1016/j.seta.2021.101380>
- [43] Senapati, T., & Yager, R. R. (2020). Fermatean fuzzy sets. *Journal of Ambient Intelligence and Humanized Computing*, 11, 663–674. <https://doi.org/10.1007/s12652-019-01377-0>
- [44] Arora, H. D., & Naithani, A. (2023). A new definition for quartic fuzzy sets with hesitation grade applied to multi-criteria decision-making problems under uncertainty. *Decision Analytics Journal*, 7, 100239. <https://doi.org/10.1016/j.dajour.2023.100239>
- [45] Dutta, P., & Konwar, A. (2024). Quintic fuzzy sets: A new class of fuzzy sets for solving multi-criteria decision-making problems under certainty. *Decision Analytics Journal*, 11, 100449. <https://doi.org/10.1016/j.dajour.2024.100449>
- [46] Mishra, A. R., Mardani, A., Rani, P., & Zavadskas, E. K. (2020). A novel EDAS approach on intuitionistic fuzzy set for assessment of health-care waste disposal technology using a parametric divergence measure. *Journal of Cleaner Production*, 272, 122807. <https://doi.org/10.1016/j.jclepro.2020.122807>
- [47] Dursun, M., Karsak, E. E., & Karadayi, M. A. (2011). A fuzzy multi-criteria group decision-making framework for evaluating health-care waste disposal alternatives. *Expert Systems with Applications*, 38(9), 11453–11462. <https://doi.org/10.1016/j.eswa.2011.03.019>
- [48] Memari, A., Dargi, A., Jokar, M. R. A., Ahmad, R., & Rahim, A. R. A. (2019). Sustainable supplier selection: A multi-criteria intuitionistic fuzzy TOPSIS method. *Journal of Manufacturing Systems*, 50, 9–24. <https://doi.org/10.1016/j.jmsy.2018.11.002>
- [49] Zheng, Y., Xu, J., & Chen, H. (2020). TOPSIS-based entropy measure for intuitionistic trapezoidal fuzzy sets and application to multi-attribute decision making. *Mathematical Biosciences and Engineering*, 17(5), 5604–5617. <https://doi.org/10.3934/mbe.2020301>
- [50] Salimian, S., & Mousavi, S. M. (2022). The selection of healthcare waste treatment technologies by a multi-criteria group decision-making method with intuitionistic fuzzy set. *Journal of Industrial and Systems Engineering*, 14(1), 205–220. [https://www.jise.ir/arti-cle\\_139146.html](https://www.jise.ir/arti-cle_139146.html)
- [51] Rani, P., Mishra, A. R., Krishankumar, R., Ravichandran, K. S., & Gandomi, A. H. (2022). A new Pythagorean fuzzy based decision framework for assessing healthcare waste treatment. *IEEE Transactions on Engineering Management*, 69(6), 2915–2929. <https://doi.org/10.1109/TEM.2020.3023707>
- [52] Alagöz, B. A. Z., & Koasoy, G. (2007). Treatment and disposal alternatives for health-care waste in developing countries: A case study in Istanbul, Turkey. *Waste Management and Research*, 25(1), 83–89. <https://doi.org/10.1109/TEM.2020.3023707>
- [53] Wang, L., & Wang, H. (2022). An integrated qualitative group decision-making method for assessing health-care waste treatment technologies based on linguistic terms with weakened hedges. *Applied Soft Computing*, 117, 205–220. <https://doi.org/10.1016/j.asoc.2022.108435>